

AL OMRANIYA TRADING CO. L.L.C.

WATER: IRON VALVES



Resilient Seated Service Gate Valve
BS / ISO / JIS standards
PN10/16 - DN15mm to DN50mm
Threaded Ends
EPDM Vulcanized Wedge



Resilient Seated Non Rising
Spindle Gate Valve
BS / DIN / ISO / AWWA
standards
PN10 / 16 - DN40mm to
DN600mm
PN25 - DN40mm to
DN300mm
Double Flange
EPDM Vulcanized Wedge



Resilient Seated Non Rising Spindle
Gate Valve
BS / DIN / ISO / AWWA standards
PN10 / 16 - DN40mm to DN300mm
PN25 - DN40mm to DN300mm
Double Spigot
EPDM Vulcanized Wedge



Resilient Seated Rising
Spindle
Gate Valve
BS / DIN / ISO / AWWA
standards
PN10 / 16 - DN40mm to
DN600mm
PN25 - DN40mm to
DN300mm
Double Flange
EPDM Vulcanized Wedge



Resilient Seated Non Rising Spindle
Gate Valve

BS / DIN / ISO / AWWA standards PN10 / 16 - DN40mm to DN600mm PN25 - DN40mm to DN300mm Electrical Actuation EPDM Vulcanized Wedge



Metal Seated Service Gate Valve

BS / DIN / JIS standards
PN10 - DN15mm to DN100mm
Threaded Ends
Brass Seal



Metal Seated Non Rising Spindle
Gate Valve

BS / DIN / ISO / AWWA standards PN10 – DN50mm to DN1200mm PN16 – DN50mm to DN1200mm Double Flange Brass Seal



Metal Seated Non Rising
Spindle
Gate Valve with Bypass or
Gearbox

BS / DIN / ISO / AWWA standards PN10 – DN400mm to DN1200mm PN16 – DN400mm to DN1200mm Double Flange Brass Seal



Metal Seated Rising Spindle Gate Valve

BS / DIN / ISO / AWWA standards PN10 – DN50mm to DN1200mm PN16 – DN50mm to DN600mm Double Flange Brass Seal



Metal Seated Non Rising
Spindle
Gate Valve

BS / DIN / ISO / AWWA standards PN10 – DN50mm to DN1200mm PN16 – DN50mm to DN1200mm Electrical Actuation Brass Seal



Resilient Seated Centreline Butterfly Valve with Bare Shaft / Lever / Gearbox

EN / DIN / ISO / AWWA standards PN10 – DN50mm to DN2200mm PN16 – DN50mm to DN1200mm Double Flange EPDM Body Bonded Liner



Resilient Seated Centreline Butterfly Valve with Bare Shaft / Lever / Gearbox

Shaft / Lever / Gearbox
EN / DIN / ISO / AWWA
standards
PN10 – DN50mm to
DN1200mm
PN16 – DN50mm to
DN1200mm
Wafer Type / Full Lugged
EPDM Body Bonded Liner



Resilient Seated Centreline Butterfly Valve with Bare Shaft / Lever / Gearbox

EN / DIN / ISO / AWWA standards PN25 – DN50mm to DN600mm Double Flange / Wafer Type / Full Lugged EPDM Body Bonded Liner



Resilient Seated Double Eccentric Butterfly Valve with Bare Shaft / Lever / Gearbox

Lever / Gearbox
EN / DIN / ISO / AWWA
standards
PN10 – DN50mm to
DN1200mm
PN16 – DN50mm to
DN800mm
Double Flange / Wafer Type /
Full Lugged
Replaceable EPDM Seal Liner



Metal Seated Double Eccentric Butterfly Valve with Bare Shaft / Lever / Gearbox

EN / DIN / ISO / AWWA standards PN10 – DN50mm to DN1200mm PN16 – DN50mm to DN800mm Double Flange / Wafer Type / Full Lugged Brass / Stainless Steel Seal



Resilient Seated Rubber Flap Check Valve

BS / DIN / ISO / AWWA standards PN10 – DN50mm to DN300mm PN16 – DN50mm to DN300mm Double Flange / Wafer Type Nylon Reinforced EPDM Disc



Metal Seated Non Slam Check Valve

BS / ISO / AWWA standards PN10 – DN150mm to DN1200mm PN16 – DN150mm to DN1200mm Double Flange Brass Seal



Resilient Seated
Underground
Fire Hydrant
BS 750 Type 1 & 2 standards
PN10/16 - DN80mm
Flanged
London Thread / Bayonet /
Instantaneous
Anti-Froze Valve